



**GANCHO Y  
GANCHO**

Diam. Rosca long. a tensar (Pulg.)	Limite de Trabajo (Lbs)	Peso de c/u (Lbs.)
1/4 x 4	400	0.30
5/16 x 4-1/2	700	0.47
3/8 x 6	1.000	0.78
1/2 x 6	1.500	1.60
1/2 x 12	1.500	2.28
5/8 x 6	2.250	2.75
5/8 x 12	2.250	3.50
3/4 x 6	3.000	3.89
3/4 x 12	3.000	5.43
3/4 x 18	3.000	8.12
7/8 x 12	4.000	8.10
1 x 12	5.000	11.93

Dimensiones en Pulgadas								
X	E	B	D	L	M	R	S	A
		cerrado		abierto	cerrado	abierto	cerrado	
0.25	0.45	1.59	1.27	11.12	7.12	11.94	7.94	4.00
0.31	0.50	1.94	1.50	12.61	8.31	13.61	9.31	4.50
0.38	0.56	2.30	1.77	16.50	10.50	17.72	11.72	6.00
0.50	0.66	2.94	2.28	18.82	11.82	20.38	13.38	6.00
0.50	0.66	2.94	2.28	30.82	17.82	32.38	19.38	12.00
0.63	0.90	3.69	2.81	20.50	13.25	22.50	15.25	6.00
0.63	0.90	3.69	2.81	32.50	19.25	34.50	21.25	12.00
0.75	0.98	4.52	3.33	22.38	14.66	24.78	17.28	6.00
0.75	0.98	4.52	3.33	34.38	20.66	36.78	23.28	12.00
0.75	0.98	4.52	3.33	46.38	26.66	48.78	29.28	18.00
0.88	1.13	5.19	3.78	36.00	22.25	38.75	25.00	12.00
1.00	1.25	5.84	4.25	37.63	23.63	40.69	26.69	12.00