



- Three meters of control cable as standard accompanies.
- Optional length of lift, push button cord and control cable besides standard is available on your request.
- Extending the load chain is prohibited with additional links.
- Steel chain containers are available as option if your lift is more than capacity of the standard container volume.

### Technical Parameters

Capacity (t)	Model	Lifting speed (m/min)	Motor Power (Kw)	No. of chain	Chain size	Net weight (Kg)
500kg	PE005S	7.8	0.8	1	6.3×19	47
1	PE010S	6.6	1.5	1	7.1×21	61
	PE010L	3.3	0.8	2	6.3×19	52
2	PE020S	6.6	3.0	1	10×30	115
	PE020L	3.3	1.5	2	7.1×21	73
3	PE030S	5.4	3.0	1	11.2×34	115
	PE030L	4.4	3.0	2	10×30	122
	PE033L	2.2	1.5	3	7.1×21	131
5	PE050S	2.7	3.0	2	11.2×34	151

### Size Specification (mm)

Model	H	A	B	D	E
PE005S	530	460	230	288	178
PE010S	650	520	260	300	176
PE010L	670	460	230	288	178
PE020S	800	615	295	430	265
PE020L	835	520	260	300	236
PE030S	845	615	295	430	265
PE030L	950	615	295	430	320
PE033L	950	520	260	350	205
PE050S	1030	615	295	430	325