



- Three meters of control cable as standard accompanies.
- Optional length of lift, push button cord and control cable besides standard is available on your request.
- Extending the load chain is prohibited with additional links.
- Steel chain containers are available as option if your lift is more than capacity of the standard container volume.

Technical Parameters

| Capacity (t) | Model | PE | | | | TE | | | | |
|--------------|---------|-----------------------|------------------|--------------|------------|----------------------|------------------|----------------|-----------------------|-------------------------|
| | | Lifting speed (m/min) | Motor Power (Kw) | No. of chain | Chain size | Travel speed (m/min) | Motor Power (Kw) | Beamwidth (mm) | Min. Radius curve (m) | N.W of standard 3m lift |
| 500kg | PET005S | 7.8 | 0.8 | 1 | 6.3×19 | 11 or 21 | 0.4 | 68-130 | 0.8 | 88 |
| | PET010S | 6.6 | 1.5 | 1 | 7.1×21 | 11 or 21 | 0.4 | 68-130 | 0.8 | 103 |
| | PET010L | 3.3 | 0.8 | 2 | 6.3×19 | | | | | 93 |
| 2 | PET020S | 6.6 | 3.0 | 1 | 10×30 | 11 or 21 | 0.4 | 82-153 | 0.9 | 164 |
| | PET020L | 3.3 | 1.5 | 2 | 7.1×21 | | | | | 122 |
| 3 | PET030S | 5.4 | 3.0 | 1 | 11.2×34 | 11 or 21 | 0.75 | 82-153 | 1 | 176 |
| | PET030L | 4.4 | 3.0 | 2 | 10×30 | | | | | 183 |
| | PET033L | 2.2 | 1.5 | 3 | 7.1×21 | | | | | 192 |
| 5 | PET050S | 2.7 | 3.0 | 2 | 11.2×34 | 11 or 21 | 0.75 | 100-178 | 1.8 | 234 |

Size Specification (mm)

| Model | H | A | B | D | E |
|---------|------|-----|-----|-----|-----|
| PET005S | 635 | 460 | 230 | 288 | 178 |
| PET010S | 650 | 520 | 260 | 300 | 176 |
| PET010L | 695 | 460 | 230 | 288 | 205 |
| PET020S | 770 | 615 | 295 | 430 | 265 |
| PET020L | 815 | 520 | 260 | 300 | 236 |
| PET030S | 830 | 615 | 295 | 430 | 265 |
| PET030L | 930 | 615 | 295 | 430 | 320 |
| PET033L | 940 | 520 | 260 | 350 | 205 |
| PET050S | 1015 | 615 | 295 | 430 | 325 |